

#### C600

VersaLink C600 Colour Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.connectkey.com**.

System Specifications	VersaLink 600/N VersaLink 600/DN	
<b>One-sided Speed</b> A4 / 210 x 297 mm	Up to 53 ppm colour and black and white	
Two-sided Speed A4 / 210 x 297 mm	Up to 50 ppm colour and black and white	
Monthly Duty Cycle <sup>1</sup>	Up to 120,000 pages / month <sup>1</sup>	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 15,000 pages	
Hard Drive	Optional 250 GB HDD	
Processor	1.05 GHz	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Role Based Permissions, Convenience Authentication Enabled, Online Support	
Device Specifications		
Electrical Requirements		
Europe	Voltage: 220-240V +/- 10 % Frequency: 50/60 Hz +/-3 % , 8A	
Power Consumption		
Continuous Printing <sup>4</sup>	800 watts or less	
Ready / Standby Mode <sup>4</sup>	85 watts or less	
Energy Saver / Sleep Mode <sup>4</sup>	0.7 watts or less	
Operating Environment		
Required Temperature Range (Storage)	0° to 35° C	
Required Temperature Range (Operating)	10° to 32° C	
Required Relative Humidity	15% to 85%	
Sound Power Levels	Operating: 7.27 B(A) or less; Standby 4.84 B(A) or less	
Sound Pressure Levels	Operating 57.4 dB(A) or less, Standby 33.5 dB(A) or less	
Boot Time (from Off to UI Ready)	As fast as 52 seconds	
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds	

Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
VersaLink C600/N and DN	427.4 mm	465.5 mm	443.4 mm	29.4 kg
550-sheet Paper Tray	420 mm	464.5 mm	123 mm	6.6 kg
High Capacity Feeder	724.2 mm	772.1 mm	459 mm	19.7 kg
Stand	724.2 mm	772.1 mm	336 mm	16.6 kg
Caster Base	724.2 mm	772.1 mm	90 mm	8.5 kg
Mailbox	450.8 mm	477.6 mm	248.0 mm	5.3 kg
Finisher	450.8 mm	411.0 mm	248.0 mm	6.8 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
VersaLink C600/N and DN	580 mm	634 mm	607 mm	35 kg
550-sheet Paper Tray	535 mm	584 mm	248 mm	8.5 kg
High Capacity Feeder	568 mm	663 mm	711 mm	38 kg
Stand	584 mm	629 mm	597 mm	28 kg
Caster Base	585 mm	619 mm	330 mm	18 kg
Mailbox	573 mm	518 mm	386 mm	7.8 kg
Finisher	573 mm	398 mm	386 mm	8.8 kg
Certifications				
	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Print				
First-print-out Time	As fast as 8 seconds colo	As fast as 8 seconds colour and black and white		
Print Resolution	Up to 1200 x 2400 dpi			
Page Description Languages	PCL <sup>®</sup> 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe <sup>®</sup> PostScript <sup>®</sup> 3 <sup>™</sup>			
Maximum Print Area	4 mm from edge of paper			
Print Features	Application Defaults Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings Two-sided Printing (as default) Xerox® Earth Smart Driver Settings			
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS			
Operating Systems	Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2 Server 2012 Mac OS® version 10.10, 10.11, & 10.12 Citrix Redhat® Enterprise Linux®			

Network Protocols	IBM® AIX® 7.2 HP-UX® 11iv3 Oracle® Solaris 11.3 Fedora Core 24 SUSE® 13.2 TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™	
	Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Mobile Solutions and Mobile Dev	vice Apps	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox <sup>®</sup> Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.	
Xerox <sup>®</sup> Print Management and Mobility Suite, Xerox <sup>®</sup> Print Management and Mobility Service	Xerox <sup>®</sup> Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
Software Solutions		
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.	
Security		
Standard Security Features	Firmware Verification Security Certificate Management Automatic Self-Signed Certificate Creation Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP) Certificate Path Validation Immediate Disk Overwrite (optional HDD) AES 256-bit Encryption FIPS 140-2 TLS/SSL SNMPv3 Smart Card Enablement (CAC/PIV/.NET) Detection of external programme falsification (XCP Plug-in) Network Authentication Access Controls Role Based Permissions Domain Filtering IP Address Filtering Port Filtering	

	Audit Log			
	Audit Log Secure Print			
Accounting				
Xerox <sup>®</sup> Standard Accou	Xerox® Standard Accounting / Network Accounting (Standard)			
Tracking	Print usage			
Accounting	<b>Xerox<sup>®</sup> Standard Accounting</b> Up to 9,999 User Accounts with HDD installed, 1,000 User Accounts without HDD installed			
	Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs Up to 14,000 accounting records (transactions)			
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>			
Accounting Options – N	etwork Accounting (Allows central server to manage all accounting)			
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements includes support for HTTPS protocol</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>			
Paper Handling				
Bypass Tray				
Capacity <sup>3</sup>	150 sheets			
Sizes	Custom sizes: 76 x 127 mm to 216 x 356 mm			
Weights	60 to 220 gsm			
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled			
Tray 1				
Capacity <sup>3</sup>	550 sheets			
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm			
Weights	60 to 220 gsm			
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled			

Up to Four Additional Trays (Optional)			
Capacity <sup>3</sup>	550 sheets		
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm		
Weights	60 to 220 gsm		
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled		
High Capacity Feeder (Optional	- only one additional 550-sheet Tray can be adde	ed to High Capacity Feeder)	
Capacity <sup>3</sup>	2,000 sheets		
Sizes	A4		
Weights	60 to 176 gsm		
Types	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled		
Total Capacity			
Standard Device Capacity <sup>3</sup>	700 sheets		
Maximum Device Capacity <sup>3</sup>	3,250 sheets		
Paper Output / Finishing	VersaLink 600/N	VersaLink 600/DN	
Capacity <sup>3</sup>	Up to 500 sheets		
Automatic Two-sided Printing	NA	Standard	
Finisher (Optional)			
Capacity <sup>3</sup>	500-sheet tray, 50-sheet stapling		
Mailbox (Optional)			
Capacity <sup>3</sup>	Four 100-sheet bins		
Device Management			
Xerox <sup>®</sup> CentreWare <sup>®</sup> Web Softw	are		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
Xerox® Embedded Web Server – Integrated Device Web Page			
Device Status	<ul> <li>Tray status/contents</li> <li>Consumables status</li> <li>Billing/Usage</li> <li>Quick Links</li> </ul>		
Print Queue Viewing	Job print queue management—view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		

Browsers	Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52	
Remote Services		
Automated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
What's In The Box		
	VersaLink C600 Colour Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 6,000 print capacity <sup>5</sup> , Black: 10,000 print capacity <sup>5</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord	

Supplies and Accessories	Quantity	Part Number	
Supplies			
Standard Capacity Print Cartridges	Black: 6,000 standard pages <sup>5</sup> Cyan: 6,000 standard pages <sup>5</sup> Magenta: 6,000 standard pages <sup>5</sup> Yellow: 6,000 standard pages <sup>5</sup>	106R03899 106R03896 106R03897 106R03898	
High Capacity Print Cartridges	Black: 12,200 standard pages <sup>5</sup> Cyan: 10,100 standard pages <sup>5</sup> Magenta: 10,100 standard pages <sup>5</sup> Yellow: 10,100 standard pages <sup>5</sup>	106R03907 106R03904 106R03905 106R03906	
Extra High Capacity Print Cartridges	Black: 16,900 standard pages <sup>6</sup> Cyan: 16,800 standard pages <sup>6</sup> Magenta: 16,800 standard pages <sup>6</sup> Yellow: 16,800 standard pages <sup>6</sup>	106R03923 106R03920 106R03921 106R03922	
Routine Maintenance Items			
Drum Cartridges	Cyan: 40,000 pages <sup>6</sup> Magenta: 40,000 pages <sup>6</sup> Yellow: 40,000 pages <sup>6</sup> Black: 40,000 pages <sup>6</sup>	108R01485 108R01486 108R01487 108R01488	
Waste Cartridge	30,000 pages <sup>6</sup>	108R01416	
Accessories			
550-sheet Feeder		097504949	
High Capacity Feeder		097504948	
Cabinet		097504955	
Stand/Casters (included with High Capacity Feeder and Cabinet)		097504954	
Finisher (500 sheets, 50-sheet stapler)		097504952	
4-Bin Mailbox (100 sheets per bin)		097504953	
Productivity Kit with 250 GB HDD		497K18360	
Wireless Network Adapter (Wi-Fi Kit)		497K16750	
External Card Reader		497K18380	

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 <sup>2</sup> Expected regular monthly throughput.
 <sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
 <sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
 <sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.
 <sup>6</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

www.xerox.com

Configurations vary by geography.

