# HP LaserJet Pro 3002dn Printer



## Get fast printing speeds and easy management tools with LaserJet Pro.

This printer is built for powerful productivity with fast speeds and reliable hardware, delivering effortless everyday use from wherever work happens so you can focus more on your business.





This printer uses dynamic security, which may be updated periodically by firmware updates. The printer is intended to be used solely with cartridges using an original HP chip. Cartridges using a non-HP chip may not function or may cease to function. More at: www.hp.com/learn/ds

## Highlights

- Instant Ink for Laser available
- Fast print speed (33 ppm A4)
- High monthly duty cycle (50,000 pages)
- Automatic two-sided printing standard
- HP Smart app and Smart Adv/Pro
- HP Wolf Pro security







## Powerful productivity.

- Support your small workteams with this smart printer, designed for up to 7 users.
- Print more efficiently. Save time, paper, and costs with fast print speed and auto two-sided printing.
- Do more in fewer steps. Simple shortcuts allow your employees to complete common tasks with just a touch.
- Get productivity in the palm of your hand. Print, scan and get time-saving Shortcuts with HP  $\,\rm Smart\, app.^1$

#### Seamless management.

- Centralise print management for your enterprise. HP Web Jetadmin makes it easy with its suite of features.  $^{\rm 2}$
- Set up your printers quickly wherever work happens. Cloud connectivity makes it easy for your IT team.
- Access your printers from a single dashboard. Smart Admin guides you through setup and gives IT visibility.  $^{\rm 3}$

## HP Wolf Pro Security.

- Get printer security out of the box. Preconfigured settings mean it's ready when you are.
- Set up and manage your printers from a single dashboard. Smart Admin makes the experience seamless.  $^{\rm 3}$
- Add a layer of security. PIN/pull option authenticates your print jobs only when you're present.
- Set configuration policies and validate settings universally with HP JetAdvantage Security Manager.<sup>4</sup>

## Hassle-free supplies management with Instant Ink.

- Enroll to save on Original HP Toner with Instant Ink. Get toner, delivery and recycling. <sup>5,6,7</sup>
- Never run out of toner with Instant Ink for laser.<sup>8</sup>
- With Instant Ink, get toner automatically delivered to workers or offices all on one consolidated  $\mathsf{bill.}^7$
- With Instant Ink, you get to select the right plans for each of your printers. Change or cancel at any time.  $^{9}\,$

## Product walkaround

## HP LaserJet Pro 3002dn Printer shown



- 1. Fast printing, up to 35 ppm, 250-sheet standard paper capacity
- 2. Built for the small workteams of up to 7 users
- 3. Automatic 2-sided printing
- 4. Pre-configured security settings
- 5. High-speed USB ports, built-in fast Ethernet
- 6. Cassette type input tray

# Accessories, Supplies and Support

Supplies	W1390A HP 139A Black Original LaserJet Toner Cartridge (Average cartridge yields 1,500 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
	W1390X HP 139X High Yield Black Original LaserJet Toner Cartridge (Average cartridge yields 4,000 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
Service and Support	UH761E 3 years Advanced Exchange (All EMEA countries Except Adriatic, Africa, CIS, EEM, Israel, Middle East, Russia, South Africa, Turkey) UH757E 3 years Next Business Day exchange (available in Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Ireland, Italy, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Spain, Sweden, Switzerland, UK) UH764E 3 years Return to Depot (available in Adriatic, Africa, CIS, EEM, Israel, Middle East, Russia, South Africa, Turkey)

# Technical specifications

Media sade   Japanese Postcard, Double Japan Postcard, Rotated: Japanese Envelope Chou #3; Japanese Envelope Cb; Envelope C5; Envelope C6; Envelope C6; Envelope C1     Media Anading   Standard Input: 1 main tray; Z50 sheets or 10 envelopes Standard output: 150-sheet output tray     Media Anadini   60 to 163 g/m <sup>2</sup> Input: capacity   Tray 1: Sheets: up to 250; Envelopes: up to 10 Maximum: Up to 250 sheets     Output: capacity   Standard (muct: 1 main tray; Z50 and the Standard output: 150-sheet output tray     Compatible coperating systems   Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit; 2 G8 available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Apple® macOS v10.15 Catalina, macOS v12 Monteresy; 2 Gi     Compatible network operating systems   Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 R2 64-bit, Windows Server 2015 R2 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 R4-bit, Linux- For more information see thttp://developers.hp.com/hp-linux-imaging-and-printing.     Minimum system requirements   Windows Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 G8 available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge.     Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey, 2 G8 H0, Internet required     Software included   No CD inbox Downloadabile Software Forn http://www.hpsmart.com     Dimensions and weight   HP Smart, HPSM,	Madel	UD Lacestate Dec 2002 de Delater
Inclusion   Met     Contrig and Contrig and Inclusion/ Part   Statume Day, Met, Controll, Honger, Meterson, Tanol Part     Inclusion/ Part   Statume Day, Meterson, Day Controll, Honger, Meterson, Tanol Part     Inclusion/ Part   Statume Day, Meterson, Day Controll, Honger, Meterson, Tanol Part     Inclusion/ Part   Statu Schronger, Statume J, Part Schronger, S		
Canadia person   Patients DR, Huls, Conselliournel, 21 Indiant LDS, Paper, Materica, Torent.     Descention   Canadian DR, Huls, Conselliournel, 21 Indiant LDS, Paper, Materica, Torent.     Descention   East CAA. General (http://indiant.2006)   Descention     Descention   East CAA. General (http://indiant.2006)   Descention     Descention   East CAA. General (http://indiant.2006)   Descention     Descention   East CAA. General (http://indiant.2006)   Descention   Descention     Descention   East CAA. General (http://indiant.2007)   Descention   Descention   Descention     Descention   Automatic Capes, Eagle (http://indiant.2007)   Descention   Descention   Descention     Patter method   Automatic Capes, Eagle (http://indiant.2007)   Descention   Descention   Descention     Statution   Automatic Marchael   Descention   Descention   Descention   Descention     Statution   Automatic Marchael   Descention   Descention   Descention   Descention     Statution   Automatic Marchael   Descention   Descention   Descention   Descention   Descention   Descention		
Print     Strettschreiding   Jace     Strettschreiding   Stock M. Aremedic byte ist spen. Stack M. Adapted byte ist spen.     Strettschreiding   Stock M. Aremedic byte ist spen. Stack M. Adapted byte ist spen.     Strettschreiding   Stock M. Adapted byte ist spen. Stack M. Adapted byte ist spen.     Strettschreiding   Stock M. Adapted byte ist spen.     Strettschreiding   Adapted Strettschreiding byte spen.     Strettschreiding   Adapted Strettschreiding byte spen.     Strettschreiding   Strettschreiding byte spen.		
Part territoriogn   Law     Prot territoriogn   Biol KM, and Witch Sam, Black KM, adalok Lip Loz 2 on     Prot territorium   Biol KM, and Witch Sam, Black KM, adalok Lip Loz 20 on     Prot territorium   Biol KM, and Witch Sam, Black KM, adalok Lip Loz 20 on Loca Lip Endedgy Lic 2020, and Biol Lin B Protein Lin Con     Month And Constant   Automative Lip Sam, Black KM, Adalok Lip Loz 20, and Lip Mark Lip Mark Lip Loz 20, and Lip Mark Lip Mark Lip Loz 20, and Lip Mark Lip Mark Lip		3 Buttons (UN, Inro, Cancel/Resume); 3 Indicator LEUS (Paper, Attention, Ioner).
Part tead   Book 04, normality to 33 ypn / Book 04, alpedy to 20 ypn     Part tead   Book 04, normality to 33 ypn / Book 04, alpedy to 20 ypn     Part teadure   Book Sect Up to 20 y 1000 ypn / Book 04, alpedy to 20 ypn / Book 04, alpedy to 20 ypn / Book 04, alpedy 120 ypn / B		
The tage off   Block Mar cools for sites in 2 race: Boor Mark steps in the site in 2 race     The tage off   Block Mar cools for sites in 2 race: Boor Mark steps in the south on Francement technology (BL); PP France 1200     Marting days off   Up to SLODD AR Excemment for monthy gauge starters: Site in 250 page.     Description of the south off   Description of the south off   Description of the south off     Description of the south off   Description of the south off   Description of the south off     Description of the south off   Description of the south off   Description of the south off     Description of the south off   Description of the south off   Description of the south off     Description of the south off   Description of the south off   Description off     Description of the south off   Description off   Description off   Description off     Description of the south off   Description off   Description off   Description off     Description off   Description off   Description off   Description off   Description off     Description off   Description off   Description off   Description off   Description off   Description off     Description off   Description off   <		
Part resultor   Box feed to store 1200 /		
Nuclei Juris Color Alexander morth gage values 2010 is 200 juris     Prester samt Stheward   Advance Alexander Morth Speet Values (Net Stranghuler, Net Standard, Net Stranghuler, Net Standard, Net S		
Autors at software interest.   Autors at agine, Samp OSE, Samp Standy, UP Shareh Ray, Sank, Shriel anywhere, UP Shareh Adam.     Straid and the stage, Samp Standy, Samp		
Sandad print languages   PLLS: PLLS: PSP. Lang. PS		
Forts and provinces   94 scalable Turry byse forts.     Deta as a   Pre-mergins Top, 4.23 mm, bith 4.23 mm, bight 4.		
Pint and Delts print   Print margins (ed.2) cm, deft. 4.22 cm, Bight. 4.23 cm, Molmung pint use. 1207 v348 cm.     Delts print   Automatic Standard   Processor gend   900 Mitz     Connectivity   Print margins (ed.2) cm. 200 Mitz   Print margins (ed.2) cm. 200 Mitz     Standard   III-Speet US down (compatible with US 2.0 specifications). 10/100Mpp Etheme.   Print Margins (ed.2) cm. 200 Mitz     Standard   III-Speet US down (compatible with US 2.0 specifications). 10/100Mpp Etheme.   Print Margins (ed.2) cm. 200 Mitz   Specifications     Standard (compatible with US 2.0 specifications). 10/100Mpp Etheme.   Print Margins (ed.2) cm. 200 Mitz   Specifications		
Daples printing   Automatic Bundhedil     Process speed   800 Hrit     ConnectMy   Standad   H-Speed USB device longatable with USB 2.0 specifications]. 10/100Mpgs Ethemet.     Mobile printing catability   HP Smart App, Apple MP Here Mode, IPS 2.12 specifications]. 10/100Mpgs Ethemet.     Mobile printing catability   HP Smart App, Apple MP Here Mode, IPS 2.19 Sengur, WD Standard, WM St, SIMP v 1/2/3, and HTSPHTPS     Network   Standad 2 SP MB Modername 75 MB     Motile printing   Standad 1 Modimum 75 MB     Motile printing   Standad 1 Modimum 75 MB     Motel specific Printing   Standad 1 Modimum 75 MB     Mode specific Printing   Standad Induit   Standad Induit     Mode specific Printing   Standad Induit   Standad Induit   Standad Induit     Mode specific Printing   Standad Induit   Standad Induit   Standad Induit     Mote specific Printing   Standad Induit   Standad Induit   Standad Induit     Mote specific Print Printing Printing Printing Printing Printing Printing Printin		
Processor gened   800 Mig     Connectivity   Science (UNIC)     Standal   Hi-Speed EBB down (compatible with USB 2.0 specification), 101 000 Mps ETheme.     Molia printing radius (LINE)   TOPIE > PAL (Info (LINE)     Standard   TOPIE > PAL (Info (LINE)     Microsoft (LINE)   TOPIE > PAL (Info (LINE)     Standard (LINE)   TOPIE > PAL (Info (LINE)     Microsoft (LINE)   Standard (LINE) <td></td> <td></td>		
Construction   He Speed USB device formgebile with USB 20 specifications? 10/1008/tps Ethernet.     Mole print cacability   He Speed USB device formgebile with USB 20 specifications? 10/1008/tps Ethernet.     Mole print cacability   He Speed USB device formgebile with USB 20 specifications? 10/1008/tps Ethernet.     Monor   Standard 256 He Mahmm. Mon Tays     Memory   Standard 256 He Mahmm. 10/n Tay     Monor y   Standard 11 Mahmm. 10/n Tay     Monor y   Standard 11 Mahmm. 10/n Tay     Mole a size   Standard 11 Mahmm. 10/n Tay     Mole a size   Standard 11 Mahmm. 10/n Tay     Mole a size   Standard Tay He Mahmm. 10/n Tay     Mole a size   Standard Tay: He main taxes     Mole a size   Standard Tay: He main taxes     Mole a size   Standard Tigs: Standard Tigs: Standard Tigs: St		
Snahed   He Seed USI device Compatible with USIR 2.0 genetations. 101/004/ps Ethemet.     Media printing castering   He Seed USI device Compatible with USIR 2.0 genetations. 101/004/ps Ethemet.     Stapport network protects   TCDMP: Med We DE Dance Media: LOD S. JR. Bengue; WS-Discowery; BOTHY DHCM AutaDP, WMS; StaMP v 1/27, and HTTPHTTPS     Memory   Standard 2.55 Mel Medinum: 256 Mel     Media harding   Standard 2.56 Mel Medinum: 256 Mel     Media harding   Standard 2.56 Mel Medinum: 256 Mel Media hardings     Media harding   Standard 1.56 Ne 2.56 Mel Media hardings     Media harding   Standard 1.56 Ne 2.56 Mel Media hardings     Media harding   Standard 1.56 Ne 2.56 Envelope Los     Media weight   6 to 1.53 g/ml     Media weight   Fore Log Mel Media harding     Media weight   Fore Log Mel		800 MHz
Peckle protect   HP Sourt Age, Age, Age, Age, Ade, Advance, Yor, Cathed     Segretiser investvers   10/1008/psc Userset.     Nemory   Sandred 2556 (B) Madmum. 1926 (H)     Nemory   Sandred 1. Madmum. 1926 (H)     Memory   Sandred 1. Madmum. 1926 (H)     Memory   Sandred 1. Madmum. 1926 (H)     Memory   Sandred 1. Madmum. 1926 (H)     Media harding   Paper (List Intert, List Meet, List Meet	· · · · · · · · · · · · · · · · · · ·	
Supportentioned network protection   100P Proc 14, bit PD Evert Medic IPD SP. Bempur. WE-Discovery, BOOTP (Int/OP Aud/B, Web, SWMP v 17/2, and HTTPH-TTPS     Mendro y   Sandwal 256 MB Meanman 256 MB     Media handling   Sandwal 256 MB Meanman 256 MB     Mendro y   Sandwal 256 MB Meanman 256 MB     Media handling   Sandwal 256 MB Meanman 256 MB     Media handling   Sandwal 256 MB Meanman 256 MB     Media handling   Gandwal 176 to 151 mm. Length 127 to 356 mm Supported finantity Aud, Asp. 46 m AB (SUIS), Dicks (27 Aud), 16K (195 x 270 mm), 16K (197 x 271 mm), 19K (197 x 291 mm), 19		
Network   10/10/00/06/s Shemert.     Memory   Sandard 25649 Meximum 254 MB     Media handling   Sandard 25649 Meximum. 14 Mai Tray     Media broger togs   Sandard 1.1 Meximum. 14 Mai Tray     Media broger   Paper full teless, plan glossy Mininu, label, envelopes, card block, postrands.     Media broger   Depare full teless, plan glossy Mininu, label, envelopes, card block, postrands.     Media broger   Sandard Togs Mininu Teless, plan glossy Mininu, label, envelopes, card block, plan Postrad forbatter, happenee Provides Chan 48, Envelope ES, Envelope ES, Envelope EG, Envelope EG, Envelope ED, Media handling     Media brading   Sandard Ingut Transur, 250 sheets to 10 envelopes Sandard Dubut 150-sheets to 10 mexings. Sandard Dubut 150-sheets to 10 sheets to 10		
Memory   Standard 255 MB Meditum: 266 MB     Media handjin   Standard 1256 MB Meditum: 1 Main Tay.     Media handjin   Standard 1 Meximum: 1 Main Tay.     Media size   Caston Injendi Welth 761 p.216 mm; Lenghi 127 to 356 mB Supported (mentol: MA, KA, SA, AK, SKG), BdG126, SGL 163 G126, SGL 163 SGL 263 G126, SGL 163 SGL 263 G126, SGL 163 SGL 263 G126, SG		
Media notify   Standard 1 Maximum: 1 Main Tray:     Media types   Paper Kud sheets, plan, glosy film, labels), envelopes, card stock, postards     Media types   Paper Kud sheets, plan, glosy film, labels), envelopes, card stock, postards     Media size   Datomer Motical Maximum: 1 Main Tray:     Media size   Datomer Motical Maximum Stock Againet Stock Maximum St	Network capabilities	10/100Mbps Ethernet.
Samther of speer trays:   Sandbart 1, Maximum 1: Hans Tay.     Media topes   Paper (GL tohest): Standing 1, Sandbard Mandels, and stark, postraads.     Media topes   Custom (matric): Neuron 2, Sandbard Mault 2, Tan Sistem Supported (matric): Al, A,	Memory	Standard: 256 MB ;Maximum: 256 MB
Media size   Pager (fur, sheets, plan, glossy film, labels), envelopes, cad stock, posscards     Media size   Custom (meth) (WH) 76 to 15 mms. Supported (meth) (AJ, AS, AS, AB, AB, SE(IS): B6(IS): 016(a) 21:63-001; 16X (195 x 270 nmk); 16X	Media handling	
Media size   Custom (metric): Width 76 126 mm; Length 127 to 358mm Supported (metric): A44.0; Ref. A4, B5100 (21 05:430); Ref. 105 (195 x 270 mm); 164 (195 x 270 mm); 1	Number of paper trays	Standard: 1 ;Maximum: 1 Main Tray
Ministration   Japanese Postcard, Double Japan Postcard Rotated, Japanese Envicinger Chou, #4, Envelope Chou, #4, Envelope CS, Envelope CG, Envelope CD,     Media handling   Standard input: I main tray, 250 sheets on 10 envelopes Standard dupts. It So sheet output tray     Media handling   Standard input: I main tray, 250 sheets on 10 envelopes Standard dupts. It So sheet output tray     Multi capacity   Tary 1 Sheets on 10 250, Envelopes up to 10 Maximum: Up to 250 sheets     Output capacity   Standard input: I nain tray, 250 sheets     Compatible operating system   Microard ************************************	Media types	Paper (Cut sheets, plain, glossy film, labels), envelopes, card stock, postcards
Media weight 60 0 163 g/m²   Input capacity Standard: Up to 250, Envelopes: up to 10 Maximum: Up to 250 sheets   Output capacity Standard: Up to 150 sheets Envelopes: Up to 10 Maximum: Up to 150 sheets   Compatible operating systems Microsoft* Windows* 11, 0, 75P1:32-bit to r64-bit, 20 Bavaliable hard disk space, Internet connection, Microsoft* Internet Explorer or Edge. Apple* mac05 v10.15 Catalina, mac03 v11 Big Sur, mac05 v12 Monterey, 2 Git Microsoft* Undows Server 2008 R2 64-bit, Windows Server 2012 R2 64-bit, Windo	Media size	Custom (metric): Width 76 to 216 mm ; Length 127 to 356mm Supported (metric): A4, A5, A5-R, A6, B5(JIS); B6(JIS); Oficio (216x340); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); L9x13 cm; 10x15cm; Japanese Postcard; Double Japan Postcard Rotated; Japanese Envelope Chou #3; Japanese Envelope Chou #4; Envelope B5; Envelope C5; Envelope C6; Envelope DL
Input capacity Tag 1: Sheets: up to 250, Envelopes: up to 10 Maximum: Up to 250 sheets   Output capacity Standard: Up to 150 sheets Envelopes: Up to 10 Maximum: Up to 250 sheets   Compatible operating systems Microsoff* Mindows* 11, 10, 791 3:2-bit of c4-bit, 2 GB available hard disk space, Internet connection, Microsoff* Internet Explorer or Edge. Apple* macOS v10.15 Catalina, macOS v12 Monterey; 2 GB compatible hard disk space, Internet connection, Microsoff* Internet Explorer or Edge. Apple* macOS v10.15 Catalina, macOS v12 Monterey; 2 GB valiable hard disk space, Internet connection, Microsoff* Internet Explorer or Edge. Microsoff* Mindow Server 2012 C4 2-bit, Windows Server 2012 C4 2-bit, Window Server 2012 C4 2-bit, Window Server 2012 C4 2-bit, Windows Server 2012 C4 2-bit, Windows Server 2012 C4 2-bit, Windows Server 2012 C4 2-bit, Window Server	Media handling	Standard input: 1 main tray; 250 sheets or 10 envelopes Standard output: 150-sheet output tray
Output capacity   Standard: Up to 150 steets: Envelopes: Up to 10 Maximum: Up to 150 steets     Compatible operating systems   Microsoft <sup>M</sup> (Mindows <sup>A</sup> 11, 10, 75 13:24 to of 64-bit, 2 G available thand disk space, Internet connection, Microsoft <sup>M</sup> Internet Explorer or Edge. Apple <sup>M</sup> macOS v10.15 Catalina, macOS v11.Big Sur, macOS v12.Monterey, 2 G is partice.     Compatible network operating systems   Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit, CPI), Windows Server 2012 64-bit, Windows Server 2016 64-bit, Linux- For more information, see https://developers.hg.com/hj.hinux-imaging-and-printing.     Minimum system requirements   Windows Microsoft <sup>M</sup> Windows <sup>A</sup> 11, 10, 75 Pi 32-bit of 64-bit, 2 GB available hard disk space. Internet connection, Microsoft <sup>M</sup> Internet Explorer or Edge.     Software included   No. CD in tox. Downloadable Software from http://www.hpc.om, http://www.hpc.om, http://www.hpc.om, http://www.hpc.om, http://www.hpc.om, http://www.hpc.om   Password-printing.     Dimensions and weight   Password-printed   Passw	Media weight	60 to 163 g/m <sup>2</sup>
Compatible operating system   Microsoft <sup>®</sup> Windows <sup>®</sup> 11, 10, 7 5P1:32-bit or 64-bit, 2 dB available hand disk space, Internet Compatible network operating systems   Windows Server 2018 64-bit, Universe for more information, see https://developers.hp.com/hp-linux-imaging-and-printing)     Compatible network operating systems   Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2016 64-bit, Linux- For more information see https://developers.hp.com/hp-linux-imaging-and-printing)     Windows Microsoft <sup>®</sup> Windows <sup>®</sup> 11, 10, 7 5P1:32-bit or 64-bit, 2 GB available hand disk space, Internet connection, Microsoft <sup>®</sup> Internet Explore or Edge.     Minimum system requirements   Microsoft <sup>®</sup> Windows <sup>®</sup> 11, 10, 7 5P1:32-bit or 64-bit, 2 GB available hand disk space, Internet connection, Microsoft <sup>®</sup> Internet Explore or Edge.     Software included   No CD in box Downloadable Education Rows Thrup/Jownh.pcom.thrum/Jownh.pcom.thru	Input capacity	Tray 1: Sheets: up to 250; Envelopes: up to 10 Maximum: Up to 250 sheets
Contraction guide up shalls HD; Internet required; Linux (For more information, see https://developers.hp.com/hp-linux-imaging-and-printing) 1	Output capacity	Standard: Up to 150 sheets Envelopes: Up to 10 Maximum: Up to 150 sheets
systems   Inttp://developers.hp.com/lp-linux-imaging-and-printing.     Minimum system requirements   Windows P11, 10, 75 P13 2-bit or 64-bit, 2 GB available hard disk space, Internet required     Software Included   No CD in box; Downloadable Software from http://www.hp.com, http://www.hp.com, http://www.hp.com, http://www.hp.com, http://www.hp.com, SNRPV1 community password-drage, 802.1x authentication     Software Included   No CD in box; Downloadable Software from http://www.hp.com, http://www.hp.com, http://www.hp.com, http://www.hp.com, http://www.hp.com, http://www.hp.com     Minimum Soft P1   Password-protected network embedded Web server; enable/disable Network ports, SNRPV1 community password change, 802.1x authentication     Printer management   HP Smart, HPSM, Web JetAdmin, admin.hp.smart.com     Dimensions and weight   7.5 Kg     Printer dimensions (W x 0 x H)   Minimum 367.0 x 398.2 x 216.2 mm; Maximum; 367.0 * 758.8 * 366.1 mm     Printer dimensions (W x 0 x H)   Minimum 367.0 x 398.2 x 216.2 mm; Maximum; 367.0 * 758.8 * 366.1 mm     Storage conditions   Temperature - 20 to 60°C     Accustics   Accustic power missions 6.5 5 I/d (/printing at 33ppm) Acoustic pressure emissions; 53 dB(A)     Accustic   Accustic power supply Up   Prover Supply Store SarXMM/weeks; Power supply Up and Wardts factive printing), 2.93 watts (ready), 1.66 watts (seep), 0.06 watts (Manual off), 0.06 watts (Auto off/Make on LAN); Typizel Electricity Consumption (FG2	Compatible operating systems	Microsoft <sup>®</sup> Windows <sup>®</sup> 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Microsoft <sup>®</sup> Internet Explorer or Edge. Apple <sup>®</sup> macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey,; 2 GB HD; Internet required; Linux (For more information, see https://developers.hp.com/hp-linux-imaging-and-printing)
Main Insystem Requirements   Mac. Apple® macOS v10.15 Catalian, macOS v11 Big Sur, macOS v12 Monterey, 2 GB HD; Internet required     Software included   No CD in box; Downloadable Software from http://www.hp.smart.com/setup, in-OS app stores.     Security management   Password-protected network rembedded Web server; enable/disable Network ports; SNMPV1 community password change; 802.1x authentication     Printer mensions and weight	Compatible network operating systems	
Security management   Password-protected network embedded Web server; enable/disable Network ports; SNMPv1 community password change; 802.1x authentication     Printer management   HP Smart, HPSM, Web JetAdmin, admin.hpsmart.com     Dimensions and weight   Finter dimensions (W x D x H)     Printer dimensions (W x D x H)   Minimum 367.0 x 398.2 x 216.2 mm; Maximum; 367.0 * 758.8 × 366.1 mm     Printer dimensions (W x D x H)   Minimum 367.0 x 398.2 x 216.2 mm; Maximum; 367.0 * 758.8 × 366.1 mm     Printer dimensions (W x D x H)   Temperature: 15 to 32.5°C Humidity: 30 to 70% RH     Storage conditions   Temperature: 0 to 60°C     Acoustics   Acoustic power emissions: 6.5 B(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)     Power   Requirements: 110-voit input voltage: 110 to 127 VAC (+1-10%), 60 Hz/50 Hz; 2C to 240 VAC (+1-10%), 60 Hz/50 Hz; Consumption 484 watts (active printing), 2.93 watts (eachy), 1.06 watts (beloge), 0.06 watts (Manual off), 0.06 watts	Minimum system requirements	Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey, 2 GB HD; Internet required
Printer management   HP Smart, HPSM, Web JetAdmin, admin.hpsmart.com     Dimensions and weight   Printer weight   Printer weight   7.5 Kg   Printer weight   Printer weight   7.5 Kg   Printer weight   7.5 Kg   Printer weight	Software included	No CD in box; Downloadable Software from http://www.hp.com, http://www.hpsmart.com/setup, in-OS app stores.
Dimensions and weight   Minimum 367.0 x 398.2 x 216.2 mm; Maximum; 367.0 x 758.8 x 366.1 mm     Printer weight   7.5 kg     Operating environment   Temperature: 15 to 32.5 °C Humidity: 30 to 70% RH     Storage conditions   Temperature: -20 to 60°C     Acoustic power emissions: 6.5 B(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)     Power   Requirements: 11 -0.volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz; Consumption: 484 watts (active printing), 239 watts (ready), 1.06 watts (sleep), 0.06 watts (Manual off), 0.06 watts (Auto 0ff/Manual On), 0.9 watts (Auto 0ff/Wake on LAN);; Typical Electricity Consumption (TED: Energy Star: 0.387 KMh/week; Power supply type: Internal (Built-in) power supply Power supply type:	Security management	Password-protected network embedded Web server; enable/disable Network ports; SNMPv1 community password change; 802.1x authentication
Printer dimensions (W x D x H)   Minimum 367.0 x 398.2 x 216.2 mm; Maximum: 367.0 x 758.8 x 366.1 mm     Printer weight   7.5 Kg     Operating environment   Temperature: 15 to 32.5°C Humidity: 30 to 70% RH     Storage conditions   Temperature: -20 to 60°C     Acoustic   Acoustic power emissions: 6.5 B(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)     Requirements: 110-volt input voltage: 110 to 127 VAC (+/ - 10%), 60 Hz/50 Hz; 220 to 240 VAC (+/ - 10%), 60 Hz/50 Hz;     Power   Consumption: 494 watts (cate point), 1.06 watts (sleep), 0.06 watts (Manual off), 0.05 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Wake on LAN);;     Typical Electricity Consumption: 494 watts (cate pupp)   Requirements: 110-volt input voltage: 10.0 387 VKI/vveek;;     Power   Consumption: 494 watts (cate pupp)   Requirements: 110-volt input voltage: 10.0 387 VKI/vveek;;     Power supply type: Internal (Built-Ini) power supply   RCM (Australia), TUV and GS Mark (Germany), BSM (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile Argeic perina, Indonesa, Singapore, Philippines, etc.     Certifications   003, Issue 6   Blue Angeic PEPAT® Silver     Blue Angeic PEPAT® Silver   Blue Angei Compliant Yees, Blue Angei DE-IUZ 205 Telecom compliance: NA, without wireless module.     Sustainable impact specifications <td>Printer management</td> <td>HP Smart, HPSM, Web JetAdmin, admin.hpsmart.com</td>	Printer management	HP Smart, HPSM, Web JetAdmin, admin.hpsmart.com
Printer weight 7.5 kg   Operating environment Temperature: 15 to 32.5°C Humidity: 30 to 70% RH   Storage conditions Temperature: -20 to 60°C   Acoustics Acoustic power emissions: 6.5 6(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)   Power Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz/50 Hz; Consumption: 484 watts (active printing), 2.93 watts (ready), 1.06 watts (sleep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Wake on LAN);; Typical Electricity (Consumption (TCC): Energy Start, 0.337 kWh/week; Power supply type: Internal (Built-in) power supply   Power Prever supply type: Internal (Built-in) power supply   RC4 (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile Argeritria, Indonesia, Singapore, Philippines, etc.   Electromagnetic emission standard: USPR32:2012 & GISPR32:2015 / ENS5032:2015 + AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/ICES 003; Issue 6   Sustainable impact specifications Mercury free   Sustainable impact specifications Mercury free   Country of origin Made in Vietnam   What's in the box <sup>3</sup> 36651F HP LaserJet Pro 3002dn Printer; HP Black LaserJet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Re	Dimensions and weight	
Operating environment   Temperature: 15 to 32.5°C Humidity: 30 to 70% RH     Storage conditions   Temperature: -20 to 60℃     Acoustic   Acoustic power emissions: 6.5 B(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)     Power   Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz/50 Hz; Consumption: 484 watts (active printing), 2.93 watts (ready), 1.06 watts (sleep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Manual On), 0.9 werts (Auto Off/Manual On), 0.9 werts (Auto Off/Manual On), 0.9 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Manual On), 0.9 werts (Auto Off/Manual On), 0.9 werts (Auto Off/Manual On), 0.9 watts (Auto Off/Manual On),	Printer dimensions (W x D x H)	Minimum 367.0 x 398.2 x 216.2 mm; Maximum: 367.0 x 758.8 x 366.1 mm
Storage conditions   Temperature - 20 to 60%     Acoustics   Acoustic power emissions: 6.5 E(A) (printing at 33ppm) Acoustic pressure emissions: 53 dE(A)     Power   Requirements: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz; 220 volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz; Consumption: 484 watts (active printing), 2.93 watts (ready), 1.06 watts (sleep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Wake on LAN);; Typical Electricity Consumption: TEC/ Energy Star: 0.337 KMM/week; Power supply type: Internal (Built-Ini power supply)     Requirements: 11.0 to 127 VAC (+/- 10%), 60 Hz/50 Hz; Consumption: TLO; Energy Star: 0.337 KMM/week; Power supply type: Internal (Built-Ini power supply)   RCM (Australia), TUV and CS Mark (Germany), BSM (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile Argeinta, Indonesa; Singapore, Philippine, etc.     Electromagnetic emission standard: (ISPR32:2012 & CISPR32:2015 / EN55032:2015 + AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B//CES 003, Issue 6     Sustainable impact specifications   Mercury free     Country of origin   Mercury free     Country of origin   Made in Vietnam	Printer weight	7.5Kg
Acoustics   Acoustic power emissions: 6.5 B(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)     Power   Requirements: 110-volt input voltage: 110 to 127 VAC (+-10%), 60 Hz/50 Hz/2220-volt input voltage: 220 to 240 VAC (+/-10%), 60 Hz/50 Hz; Consumption: 484 watts (active prios), 639 watts (steep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Wake on LAN);; Typical Electricity Consumption (TEC): Energy Star: 0.387 kWh/week; Power supply type: Internal (Built-in jo power supply ype: Internal (Built-in jo power supply ype: Power supply type: Certifications   RCM (Australia), TUV and 65 Mark (Germany), BSM (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star: UL, Paraguay, Chile Argentina, Indonesia, Singapore, Thilippines, etc. Electromagnetic emission standard: CISPR32:2012 & CISPR32:2015 / EN55032:2015 + AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/(CES 003, Issue 6 Blue Angel: EPEAT® Silver Blue Angel: emplatives, Blue angel DE-UZ 205 Telecom compliance: NA, without wireless module.     Sustainable impact specifications   Mercury free Outry of origin   Mercury free 36651F HP Laser Jet Pro 3002dn Printer; HP Black Laser Jet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord	Operating environment	Temperature: 15 to 32.5°C Hunidity: 30 to 70% RH
Acoustics   Acoustic power emissions: 6.5 B(A) (printing at 33ppm) Acoustic pressure emissions: 53 dB(A)     Power   Requirements: 110-volt input voltage: 110 to 127 VAC (+-10%), 60 Hz/50 Hz/2220-volt input voltage: 220 to 240 VAC (+/-10%), 60 Hz/50 Hz; Consumption: 484 watts (active prios), 639 watts (steep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Wake on LAN);; Typical Electricity Consumption (TEC): Energy Star: 0.387 kWh/week; Power supply type: Internal (Built-in jo power supply ype: Internal (Built-in jo power supply ype: Power supply type: Certifications   RCM (Australia), TUV and 65 Mark (Germany), BSM (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star: UL, Paraguay, Chile Argentina, Indonesia, Singapore, Thilippines, etc. Electromagnetic emission standard: CISPR32:2012 & CISPR32:2015 / EN55032:2015 + AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/(CES 003, Issue 6 Blue Angel: EPEAT® Silver Blue Angel: emplatives, Blue angel DE-UZ 205 Telecom compliance: NA, without wireless module.     Sustainable impact specifications   Mercury free Outry of origin   Mercury free 36651F HP Laser Jet Pro 3002dn Printer; HP Black Laser Jet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord		
Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/S0 Hz; 220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz/S0 Hz; Consumption: 484 watts (active printing), 233 watts (ready), 1.06 watts (sleep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Wanual On), 0.9 watts (Auto Off/Wake on LAN);; Typical Electricity (Consumption (TEC): Energy Star: 0.337KWh/week;; Power supply type: Internal Built-in) power supply     Retrifications   RCM (Australia), TUV and GS Mark (Germany), BSN (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile Argentina, Indonesia, Singapore, Philippines, etc.     Letcromagnetic emission standard: CISPR32:2012 & CISPR32:2015 / ENS5032:2015 + AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/ICES 003, Issue 6     Sustainable impact specifications   Mercury free     Country of origin   Made in Viteriam     What's in the box <sup>3</sup> 3G651F HP LaserJet Pro 3002dn Printer; HP Black LaserJet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord		
RCM (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile Argentina, Indonesia, Singapore, Philippines, etc.   Certifications Electromagnetic emission standard: CISPR32:2012 & CISPR32:2012 & EN55032:2015+AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/CES 003, Issue 6 Blue Angel: EPEAT® Silver Blue Angel compliant: Yes, Blue Angel DE-UZ 205 Telecom compliance: NA, without wireless module.   Sustainable impact specifications Mercury free   Country of origin Made in Vietnam   What's in the box <sup>3</sup> 3G651F HP LaserJet Pro 3002dn Printer; HP Black LaserJet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord		Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz/50 Hz;220-volt input voltage: 220 to 240 VAC (+/- 10%), 60 Hz/50 Hz; Consumption: 484 watts (active printing), 2.93 watts (ready), 1.06 watts (sleep), 0.06 watts (Manual off), 0.06 watts (Auto Off/Manual On), 0.9 watts (Auto Off/Wake on LAN);; Tvoical Electricity Consumption (TEC): Energy Star: 0.387 WM/hyeek;
Country of origin   Made in Vietnam     What's in the box <sup>3</sup> 3G651F HP LaserJet Pro 3002dn Printer; HP Black LaserJet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord	Certifications	RCM (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile, Argentina, Indonesia, Singapore, Philippines, etc. Electromagnetic emission standard: CISPR32:2012 & CISPR32:2015 /EN55032:2012 & EN55032:2015+AC:2016 - Class B; EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/CES-003, Issue 6 Blue Angel; EPEAT® Silver Blue Angel; COMPLIAN Ves, Blue Angel DE-UZ 205
What's in the box <sup>3</sup> 3G651F HP Laser Jet Pro 3002dn Printer; HP Black Laser Jet Toner Introductory Cartridge (yield ~ 1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord	Sustainable impact specifications	Mercury free
What's in the box <sup>3</sup> 3G651F HP Laser Jet Pro 3002dn Printer; HP Black Laser Jet Toner Introductory Cartridge (yield ~ 1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord	Country of origin	Made in Vietnam
Warranty One year limited warranty. Warranty and support options vary by product, country and local legal requirements.	What's in the box <sup>3</sup>	3G651F HP Laser Jet Pro 3002 dn Printer; HP Black Laser Jet Toner Introductory Cartridge (yield ~1000 pages); Setup Guide; Reference Guide; Regulatory Flyer; Warranty Guide; Power cord
	Warranty	One year limited warranty. Warranty and support options vary by product, country and local legal requirements.

#### Footnotes

<sup>1</sup> Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only, and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. See details at http://www.hpsmart.com. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores. Fax capabilities are for sending a fax only. After 2 years, monthly fee applies to continue advanced features with HP Smart Advance. HP Smart Advance is not available in all countries. For more information, see http://www.hpsmart.com.

<sup>2</sup> HP Web Jetadmin is available for download at no additional charge at http://www.hp.com/go/webjetadmin.

<sup>3</sup> Easy setup and manage - Requires use of Smart Admin Dashboard for printer setup and onboarding of users.

<sup>4</sup> HP JetAdvantage Security Manager must be purchased separately. To learn more, please visit http://www.hp.com/go/securitymanager.

<sup>5</sup> Recycling: Program availability varies. Original HP cartridge return and recycling is currently available in more than 60 countries, territories and regions in Asia, Africa, Europe, and North and South America through the HP Planet Partners program. For details, see http://www.hp.com/recycle.

<sup>6</sup> Save up to 50% on toner (mono) – Based on monthly subscription cost of HP Instant Ink monochrome toner service 1,500-page plan without purchase of additional sets of pages compared to cost per page to print ISO/IEC 24711 pages on most in-class, traditional A4 monochrome toner cartridge printers <€494 and MFPs priced and <€672 using original standard-capacity integrated cartridges (toner and drum in one cartridge). Average CPP per country used to determine percent savings claim versus CPP for HP Instant Ink. Sale prices not considered for this study. Printers which only use XL cartridges excluded due to non-standard hardware & supplies model. Keypoint Intelligence September 2021 study commissioned by HP, based on publicly available information as of August 18, 2021. Printers selected by market share in IDC Quarterly Hardcopy Peripherals Tracker – Final Historical 2021Q2. For details: www.keypointintelligence.com/HPInstantInk.

<sup>7</sup> Automatic delivery and consolidated bill: Printers require direct connection to the Internet for program participation. Internet access sold separately.

<sup>8</sup> Never run out: Based on plan usage, Internet connection to eligible HP printer, valid credit/debit card, email address, and delivery service in your geographic area.

<sup>9</sup> Change or cancel: Change or cancel your plan at any time online. If you decide to cancel your HP Instant Ink you can go back to using HP original Standard or XL cartridges. Plan upgrades are effective immediately and the charges will be applied retrospectively or in the next billing cycle, depending on user choice. Plan downgrades and cancellations are effective after the last day of the current billing period. For full details go to

http://www.hpinstantink.com/terms. <sup>10</sup> Change or cancel: Change or cancel your plan at any time online. If you decide to cancel your HP Instant Ink you can go back to using HP original Standard or XL cartridges. Plan upgrades are effective immediately and the charges will be applied retrospectively or in the next billing cycle, depending on user choice. Plan downgrades and cancellations are effective after the last day of the current billing period. For full details go to http://www.hpinstantink.com/terms.

#### Technical specifications disclaimers

<sup>1</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

document complexity. <sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>3</sup> For yield information on the cartridge included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.



© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ro-en August 2022

