HP LaserJet Tank MFP 2602-2606 Printer series







Get high-quality printing with ultra-low cost per page.

- Engineered for high-volume printing pre-filled with 5,000 pages of toner in the tank.¹
- Help to save on refills with ultra high yield HP Toner Reload Kit.
- Deliver exceptional quality with sharp text and bold blacks, page after page.

Easy toner refill in 15 sec with Original HP Toner²

- Easily refill Original HP Toner in 15 seconds.²
- Less downtime with 2,500 and 5,000 page HP Toner refill options.¹
- The Original HP Toner Reload Kit has an unique design, made with over 75% less plastic.³

Full features for powerful productivity.

- Speed through multipage documents with automatic two-sided printing.
- Print, scan, and share anytime, anywhere with HP Smart app.⁴
- Low maintenance with long-life up to 50,000 page imaging drum.⁵

Product walkaround

LaserJet Tank MFP 2604sdw shown

- 1. 40-sheet auto document feeder
- 2. Sharp text and consistent printing
- 3. Automatic two-sided printing
- 4. HP Smart Advance
- 5. Pre-filled with up to 5000 pages of Original HP Toner
- 6. Up to 50,000 pages Imaging Drum
- 7. Dual-band Wi-Fi® with self reset & Bluetooth LE
- 8. Built-in Fast Ethernet
- 9. Print speed up to 22 ppm (A4)
- 10. HP WOLF Security Essential
- 11. 250-sheet input tray
- 12. Smart-guided buttons



Series at a glance





Model	HP LaserJet Tank MFP 2604dw Printer	HP LaserJet Tank MFP 2604sdw Printer	
Product number	381V0A	381V1A	
Functions	Print, co	Print, copy, scan	
Print speed	Black (A4, normal): Up to 22 ppm	Black (A4, normal): Up to 22 ppm; Black (A4, duplex): Up to 14 ipm	
Connectivity		Hi-Speed USB (compatible with USB 2.0 specifications); Ethernet 10/100 Base-TX; 802.11a/b/g/n (2.4/5 GHz) Wi-Fi radio + BLE	
Recommended monthly page volume	250-	250-2500	

Configurable Items, Accessories, Supplies and Support

Supplies	W1530A HP 153A Black Original LaserJet Tank Toner Reload Kit (~2,500 pages)
	W1530X HP 153X Black Original LaserJet Tank Toner Reload Kit (~5,000 pages)
Service and Support	U04TNE 3 years Standard Exchange (available in All EMEA countries Except Adriatic, Africa, CIS, EEM, Israel, Middle East, Russia, South Africa, Turkey) U04TKE 3 years Next Business Day Exchange (available in Austria, Belgium, Czech Rep, Denmark, Finland, France, Germany, Greece, Ireland, Italy, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Spain, Sweden, Switzerland, UK) U04TSE 3 years Return to Depot (available in Adriatic, Africa, CIS, EEM, Israel, Middle East, Russia, South Africa, Turkey)

Technical specifications

HP LaserJet Tank MFP 2604dw Printer	HP LaserJet Tank MFP 2604sdw Printer	
381V0A	381V1A	
Icon LCD; 3 lights (Media, Lid open, Wifi); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power)	Icon LCD; 2 lights (Media, Lid open); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power)	
Laser		
Black (A4, ready): As fast as 8 sec; Black (A4, sleep): As fast as 8.4 sec		
Black (best) : Up to 600 × 600 dpi ; Technology : 600 × 600 dpi; 600 × 400 dpi		
Up to 25,000 pages A4; Recommended monthly page volume: 250-2500		
Automatic duplex printing, HP Auto-On/Auto-Off, HP Smart App		
PCLmS; URF; PWG		
Print margins Top: 2 mm, Bottom: 2 mm, Left: 2 mm, Right: 2 mm; Maximum print	area: 215.9 x 355.6 mm	
Automatic		
Black (A4): Up to 14 cpm	Black (A4): DM-EMEA: Up to 14 cpm; DM-NA/AP: Up to 22 cpm	
	Normal (A4): Up to 19 ppm (b&w), up to 10 ppm (color)	
JPEG, RAW(BMP), PNG, TIFF, PDF		
Scanner type: Flatbed, ADF (Optional); Scan technology: Contact Image Sensor (CIS Version 2.1; Duplex ADF scanning: No; Scan size maximum (flatbed): 216 x 297 mm); Scan input modes : HP Smart App; and user applications via Twain; Twain version : n; Optical scan resolution : Up to 600 dpi	
150 to 1500		
Maximum media size (flatbed): 216 x 297 mm; Minimum media size (ADF): 148 x 2	10 mm Maximum media size (ADF) : 216 x 356 mm	
24-bit / 256		
500 MHz		
	302.11a/b/g/n (2.4/5 GHz) Wi-Fi radio + BLE	
built-in WiFi 802.11b/g/n (2.4/5GHz)		
HP Smart App; Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing		
TCP/IP: IPv4; IPv6; LPD; SLP; Bonjour; WS-Discovery; BOOTP/DHCP/AutoIP; SNMP v	1/2/3;HTTP/HTTPS; UDP; IPP	
Ethernet 10/100Base-TX; built-in WiFi 802.11b/g/n (2.4/5GHz)		
Standard: 64 MB; Maximum: 64 MB SDRAM		
Standard: 64 MB; Maximum: 64 MB SDRAM		
Standard: 64 MB; Maximum: 64 MB SDRAM Standard: 1 ; Maximum: 1 Input Tray		
Standard: 1 ; Maximum: 1 Input Tray		
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable		
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets t support transparency Maximum: Up to 100 sheets	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; n	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets at support transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit;	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; m Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ts support transparency Maximum: Up to 100 sheets aacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; printing) Idisk space, Internet connection, Microsoft® Internet Explorer or Edge.:	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; not Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2008 R2 64-bit (SP1), Windows Chirorsofte Windows Server 2008 R2 64-bit (SP1), Windows Server 2008 R2	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets at support transparency Maximum: Up to 100 sheets acOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; brinting) Idisk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; mac0S 10.15 Catalina; mac0S 11 Big Sur; r Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows; Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® mac0S v10.15 Catalina, mac0S v11 Big Sur, mac0S v12 Monterey; 2 G No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cd Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ts support transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required om of EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest,	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ts support transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required om of EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest,	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ts support transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required om of EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest,	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ts support transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required om of EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest,	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; not Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SMPPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ts support transparency Maximum: Up to 100 sheets aacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) Idisk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required om d EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by sout; Secure Wi-Fi setup	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; not Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Chirux (For more information see http://developers.hp.com/hp-linux-imaging-and-windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GN CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255 mm	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets ac Standard, 40 sh	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; not Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc. Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default: OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets at support transparency Maximum: Up to 100 sheets acOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) Idisk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required om d EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by ond SMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; n Windows Server 2008 R2 64-bit, Windows, Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows; Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GC of Din box; Downloadable Software from http://www.hp.com or http://123.hg. Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, a Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 60°C Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets at support transparency Maximum: Up to 100 sheets accOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required by d EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; n Windows Server 2008 R2 64-bit, Windows, Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows; Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GC of Din box; Downloadable Software from http://www.hp.com or http://123.hg. Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, a Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 60°C Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A)	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets at support transparency Maximum: Up to 100 sheets accOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required by d EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protect default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 60°C Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A) Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz n Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: KED®).	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets at support transparency Maximum: Up to 100 sheets accOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required and EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac: Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey, 2 GNo CD in box; Downloadable Software from http://www.hp.com or http://123.hp.cc. Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protect default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 60°C Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A) Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz n Max 264V), 50 - 60Hz n ominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready: 2.7w, Sleep: 0.51w, Manual Off: 0.05w; Typical Electricity Consumption (TEC)®: Energy Star: 0.194Kwh/week; Blue Angel: 0 Power supply type: Internal (Built-in) power supply HP Auto-On/Auto-Off Technology; Instant-on Technology RCM (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India) approvals, CE Marking, FCC, Energy Star, UL, Paraquay, Chile, Argentina, Indonesia, inconsistent and constru	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets tsupport transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required MC EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w; XC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. ITS - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017; ISI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; n Windows Server 2008 R2 64-bit, Windows, Server 2008 R2 64-bit (SP1), Windows Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; Oscure Boot, Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protecte default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, a Active FW update, Admin password by default, Cipher & TLS selection; Account lock HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 368 X 326 X 255 mm; Maximum: 368 X 390.5 X255mm 7.9kg Temperature: 15 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 60°C Acoustic power emissions: 6.3 B(A); Acoustic pressure emissions: 49 dB(A) Requirements: 110V - 127V nominal @ +/-10% (min 99V, max 140V), 50 - 60Hz n Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Consumption: Active printing: 390w, Ready: 2.7w, Sleep: 0.51w, Manual Off: 0.05w; Typical Electricity Consumption (TEO)s: Energy Star: 0.194Kwh/week; Blue Angel: 0 Power supply type: Internal (Built-in) power supply HP Auto-On/Auto-Off Technology; Instant-on Technology RCM (Australia), TuV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India) approvals, CE Marking, FCC, Energy Star: Ul, Paraguay, Chile, Argentina, Indonesia; Electromagnetic emission standard: (CSPR3:2:2015 & CISPR 3:2:2016 (ENS503:22) (ECT) (ERT)	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets tsupport transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required MC EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w; XC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. ITS - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017; ISI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; n Windows Server 2008 R2 64-bit, Windows, Server 2008 R2 64-bit (SP1), Windows, Linux (For more information see http://developers.hp.com/hp-linux-imaging-and- Windows: Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOs v10.15 Catalina, macOS v12 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOs v10.15 Catalina, macOS v12 Big Sur, macOS v12 Monterey; 2 GB available hard Mac Apple® macOs v10.15 Catalina, macOS v12 Monterey; 2 GB available hard Mac Apple® macOs v10.15 Catalina, macOS v12 Monterey; 2 GB available hard Mac Apple® macOs v10.15 Catalina, macOS v12 Monterey; 2 GB available hard Mac Apple® v10.15 Catalina,	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets tsupport transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required MC EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w; XC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. ITS - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017; ISI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; not Windows Server 2008 R2 64-bit, Windows Server 2008 R2	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets tsupport transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required Me EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w; 203Kwh/week; KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. 115 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017; ISI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1	
Standard: 1; Maximum: 1 Input Tray Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope Custom (metric): 102 x 152 to 215.9 x 355.6 mm; Supported (metric): A6; A5; A4; ADF: A4, Letter, Legal Standard input: 250-sheet input tray Optional input: Not applicable 60 to 163 g/m²; ADF: 60 to 90 g/m² Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; n Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64	Standard input: 250-sheet input tray Optional input: Not applicable ADF: Standard 40 sheets Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets tsupport transparency Maximum: Up to 100 sheets nacOS 12 Monterey; Linux Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Orinting) I disk space, Internet connection, Microsoft® Internet Explorer or Edge.; B HD; Internet required MC EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, out; Secure Wi-Fi setup Minimum 418 X 345 X 311.4 mm; Maximum: 418 X 398.5 X 311.4mm 9.5 kg Minimum 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w; XC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European Singapore, Philippines, etc. ITS - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017; ISI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1	
	Icon LCD; 3 lights (Media, Lid open, Wifi); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power) Laser Black (A4, normal) Up to 22 ppm; Black (A4, duplex): Up to 14 ipm Black (A4, ready): As fast as 8 sec; Black (A4, sleep): As fast as 8.4 sec Black (best): Up to 600 × 600 dpi; Technology: 600 × 600 dpi; 600 × 400 dpi Up to 25,000 pages A4; Recommended monthly page volume: 250-2500 Automatic duplex printing, HP Auto-On/Auto-Off, HP Smart App PCLmS; URF; PWG Print margins Top: 2 mm, Bottom: 2 mm, Left: 2 mm, Right: 2 mm; Maximum print Automatic Black (A4): Up to 14 cpm JPEG, RAW(BMP), PNG, TIFF, PDF Scanner type: Flatbed, ADF (Optional); Scan technology: Contact Image Sensor (CIS Version 2.1; Duplex ADF scanning: No; Scan size maximum (flatbed): 216 × 297 mm; 150 to 1500 Maximum media size (flatbed): 216 × 297 mm; Minimum media size (ADF): 148 × 224-bit / 256 500 MHz Hi-Speed USB (compatible with USB 2.0 specifications; Ethernet 10/100 Base-TX; & built-in WiFi 802.11b/g/n (2.4/5GH2) HP Smart App; Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing TCP/IP: IPv4; IPv6; LPD; SLP; Bonjour; WS-Discovery; B00TP/DHCP/AutoIP; SNMP v	

Footnotes

- 1 Actual yield varies considerably based on content of printed pages and other factors. Average based on ISO/IEC 19752 and continuous printing. Additional printed pages require toner reload. For details see www.hp.com/go/learnaboutsupplies.
- ² When used in accordance with instructions. Average reload time based on HP internal testing.
- ³ Over 75% plastic reduction is calculated by comparing the weight of the plastic in HP Neverstop Laser 103/143 A/AD and HP Laser NS 108 A/AD Toner Reload Kit and its packaging.
- 4 Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. See details at HPSmart.com. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores.

 The yield of imaging drum is approximately 50,000 single-sided pages (letter or A4 size paper). There are many factors that determine the actual drum useful life, such as temperature, humidity, type of paper, type of toner used
- and other variables. The imaging drum unit is replaceable through authorized service provider.

Technical specifications disclaimers

- 1 Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity
- ² Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ³ HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; May require a firmware upgrade.
- ⁴ Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; Subscription may not be available in all countries. See details at: HPSmart.com; Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores.
- ⁵ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.
- ⁶ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.
- 7 HP Black Original Laser Jet Tank Imaging Drum (introductory ~5,000 page black toner yield provided). For yield information included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.

