

OPTIMAL PRINT AND SCAN PRODUCTIVITY FROM A COLOUR MULTI-FUNCTION PRINTER WITH DIRECT CLOUD CONNECTIVITY



i-SENSYS MF750 Series

Designed for small businesses or individuals, the Canon i-SENSYS MF750 Series delivers optimised productivity for printing and scanning.

Ultimate productivity

Work faster by printing and scanning at speeds of up to 33ppm and 100ipm (A4), as well as utilising a wide range of media handling with the ability to scan small documents such as cheques and receipts

Built-in cloud connectivity

Centralise print management with support for Universal Print by Microsoft and access documents directly from cloud storage services: Google Drive, DropBox and OneDrive



**ULTIMATE
PRODUCTIVITY**



**INTUITIVE USER
EXPERIENCE**



**BUILT-IN CLOUD
CONNECTIVITY**



RELIABLE SECURITY

Intuitive user experience

Streamline workflows with drag and drop icons to customise the display and create one-touch shortcut buttons with Application Library apps

Reliable security

Advanced system verification protects the device from hacking and virus threats as soon as you start up, while Secure PIN restricts access to sensitive documents

Canon

RANGE FEATURE STEP UP CHART



i-SENSYS MF752Cdw



i-SENSYS MF754Cdw

Fax		●
A4 print speed	33ppm	33ppm
Display	12.7cm colour touch screen	12.7cm colour touch screen
Secure PIN print	●	●
Automatic duplex printing	●	●
Built-in cloud connectivity	●	●
Application Library	●	●
Single pass duplex scan	●	●

OPTIONAL ACCESSORIES

PAPER FEEDER PF-K1

- Additional 550 sheet paper cassette, 1 unit can be added to main unit.

Telephone 6 Kit (for MF754Cdw)

- Optional telephone handset for fax function.

TECHNICAL SPECIFICATIONS

i-SENSYS MF750 Series

Machine type	Colour Laser All-in-One
Available functions	MF754Cdw: Print, Copy, Scan and Fax MF752Cdw: Print, Copy and Scan
PRINTER	
Print speed	Single sided : Up to 33 ppm (A4) Up to 60 ppm(A5-Landscape) Double sided : Up to 29.5 ipm (A4)
Printing method	Colour laser beam printing
Print resolution	Up to 1200 x 1200 dpi
Warm-up time	Approx. 14 seconds or less from power on
First Print Out Time	Colour approx.: 7.1 seconds or less Mono approx.: 7.1 seconds or less
Printer languages	MF754Cdw: UFR II, PCL 5c ² , PCL6, Adobe® PostScript3 MF752Cdw: UFR II, PCL 5c ² , PCL6
Fonts	MF754Cdw: 45 PCL fonts 136 PostScript fonts MF752Cdw: 45 PCL fonts
Print margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)
Toner saver mode	Yes
Advanced printing features	Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG) Microsoft Universal Print support IOS: AirPrint, Canon PRINT Business app Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app
COPIER	
Copy speed	Single sided (A4): Up to 33 ppm Double sided (A4): Up to 29 ipm
First Copy Output Time (FCOT)	ADF (A4): Colour Approx. 8.8 seconds or less Mono Approx. 7.6 seconds or less Platen (A4): Colour Approx. 9.4 seconds or less Mono Approx. 8.3 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text/Photo/Map (Default),Text/Photo/Map (quality), Printed Image, Text
Double sided copying	2-sided to 2-sided (Automatic)
Multiple copy	Up to 999 copies
Reduction / Enlargement	25-400% in 1% increments
Other features	Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy, Reserved copy
SCANNER	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Scan speed	Single sided mono: 50ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Double sided mono: 100ipm (300x300dpi) Double sided colour: 80ipm (300x300dpi) Single sided mono: 40ipm (300x600dpi) Single sided colour: 20ipm (300x600dpi) Double sided mono: 80ipm (300x600dpi) Double sided colour: 40ipm (300x600dpi)
Colour scanning depth	24 bit/24 bit (input/output)
Greyscale	256 levels
Compatibility	TWAIN ¹ , WIA, ICA
Max. scan width	216mm
Scan to E-mail	TIFF/JPEG/PDF/Compact PDF/Searchable PDF
Scan to PC	
Scan to USB memory key	
Scan to FTP	
Scan to Cloud¹	TIFF/JPEG/PDF/PNG ²
IFAX	ITU-T.37
FAX	
Modem speed	33.6 Kbps (Up to 3 seconds/page ³)
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
FAX memory	Up to 512 pages ⁴
Speed dials	Up to 281 dials
Group dials/destinations	Max. 299 dials / Max. 299 destinations
Sequential broadcast	Max. 310 destinations
Memory backup	Permanent fax memory backup (Backup with flash memory)
Double sided faxing	Yes (Transmit and Receive)
Other features	Sender's Name (TTI), Direct Send, Review, TX Report, Sequential Broadcasting
MEDIA HANDLING	
Scanner type	Platen, 2-sided ADF (single pass)
Paper input (Standard)	250-sheet cassette 50-sheet multi-purpose tray 50-sheet ADF
Paper input (Option)	550-sheet cassette
Maximum paper input capacity	850-sheet cassette
Paper output	150-sheet
Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Label, Post card, Envelope
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5, Monarch), Custom sizes: Min. 98 x 148 mm Max. 216.0 x 356.0 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min 76.0 x 127 mm Max. 216.0 x 356.0 mm. Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Custom sizes: Min. 100 x 148 mm Max. 216.0 x 356.0 mm. ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 48 x 85.0 mm Max 216.0 x 355.6 mm

Media weights	Cassette (standard and optional): 60 to 163 g/m ² (Up to 200 g/m ² with Coated paper) Multi-purpose tray: 60 to 176 g/m ² (Up to 200 g/m ² with Coated paper) ADF: 50 to 105 g/m ²
Double sided printing	Automatic Cassette: A4, A5, A6, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 148 x 148 mm Max. 216 x 356 mm 60 to 200 g/m ²
INTERFACE & SOFTWARE	
Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Operating System compatibility	Windows [®] 11 / Windows [®] 10 / Windows [®] 8.1 / Server [®] 2022 / Server [®] 2019 / Server [®] 2016 / Server [®] 2012R2 / Server [®] 2012 Mac OS X version 10.12 & up Linux ⁵
Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Scan: Push Scan: File: FTP (TCP/IP), SMB3.0 (TCP/IP) E-mail/fax: SMTP (send), POP3 (receive) Pull Scan: TCP/IP Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IPsec, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPSS) Security (wireless): Infrastructure Mode: WEP64/128 bit, WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA-EAP(AES), WPA2-EAP(AES) Access Point Mode: WPA2-PSK(AES)
Software and printer management	MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, IW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Application Library
GENERAL FEATURES	
Recommended Monthly Print Volume	750 - 4,000 pages per month
Duty cycle	Max. 50,000 pages per month ⁶
Processor Speed	1200MHz x 2
Memory	1GB
Control panel	12.7 cm LCD Colour Touch Screen
Dimensions with trays (W x D x H)	425 mm x 461 mm x 430 mm
Installation space (W x D x H)	625 mm x 1,117 mm x 991 mm
Weight	MF752Cdw Approx. 23.30 Kg MF754Cdw Approx. 23.60 kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V(±10%) 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. 1.380 W Active printing: Approx. 700W Standby: Approx. 24.0 W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.30 kWh/week10 (230V) For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
Noise Levels	Sound Pressure ⁷ : Active: Simplex 51dB / Duplex 51dB (BW), 50dB (CL) Standby: 29 dB Sound Power ⁸ : Active: 65dB or less Standby: 41dB or less
CONSUMABLES	
Cartridges	Cartridge 069 Black (2,100 pages ⁹) Cartridge 069H Black (7,600 pages ⁹) Cartridge 069 Cyan (1,900 pages ⁹) Cartridge 069H Cyan (5,500 pages ⁹) Cartridge 069 Magenta (1,900 pages ⁹) Cartridge 069H Magenta (5,500 pages ⁹) Cartridge 069 Yellow (1,900 pages ⁹) Cartridge 069H Yellow (5,500 pages ⁹)
ACCESSORIES/ OPTIONS	
Items	MF754Cdw: PAPER FEEDER PF-K1 (550-sheet cassette) TEL 6 Kit Long Cord (Telephone handset) MF752Cdw: PAPER FEEDER PF-K1 (550-sheet cassette)

- Notes:**
- Subscription to a third party cloud service is required, and subject to their party terms and conditions.
 - Commands supported only. Third party driver or direct printing from application required.
 - Scan by MF Scan Utility or Canon PRINT Business
 - Based on ITU-T Standard Chart No. 1
 - Web distribution only. Linux support printing only.
 - Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
 - Declared noise emission in accordance with ISO 9296
 - Based on ISO/IEC 19798
 - Printer ships with Black: 2,000 pages, C/M/Y: 1,200 pages starter cartridges
 - As per US ENERGY STAR[®] version 3.0.



OPTIMAL PRINT AND SCAN PRODUCTIVITY FROM A COLOUR MULTI-FUNCTION PRINTER WITH DIRECT CLOUD CONNECTIVITY

Designed for small businesses or individuals, the Canon i-SENSYS MF750 Series delivers optimised productivity for printing and scanning.



PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS MF754Cdw	5455C020AA	8714574670928
i-SENSYS MF752Cdw	5455C017AA	8714574670898

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
PAPER FEEDER PF-K1	5693C001AA	4549292201086
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910
Telephone 6 Kit UK (CW)	0752A053AA	4960999453897
Telephone 6 Kit SA (CW)	0752A055AA	4960999453927

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 069 Black	5094C002AA	4549292196771
Cartridge 069H Black	5098C002AA	4549292196924
Cartridge 069 Yellow	5091C002AA	4549292196689
Cartridge 069H Yellow	5095C002AA	4549292196801
Cartridge 069 Magenta	5092C002AA	4549292196719
Cartridge 069H Magenta	5096C002AA	4549292196856
Cartridge 069 Cyan	5093C002AA	4549292196740
Cartridge 069H Cyan	5097C002AA	4549292196887



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2022