

## ML750e

Ultra-compact LED projector









- HD Ready and LED technology Great for movies, gaming and PC-free presentations
- Great connectivity HDMI, MHL, micoSD and built in speaker
- Built in media play and optional wireless presentations
- Compact & Lightweight < 0.4kg

The ML750e ultra-compact portable LED projector is easily transportable between your home and office. This tiny projector weights less than 0.4kg and comes with a convenient carry bag. Watch HD  $\,$ 

movies, play video games or even present that winning presentation, the ML750e has everything you need to impress your audience.



## **Specifications**

Display/image DIPTM Display technology

Resolution WXGA (1280x800) Brightness (HK/ANSI) 700/450 Contrast ratio 20,000:1 16:10 Native aspect ratio Aspect ratio - compatible 4:3.16:9 Keystone correction - vertical +/-40°

Horizontal scan rate 15.375 ~ 91.146Khz 24 ~ 85(120 for 3D)Hz Vertical scan rate

85% Uniformity

0.43m ~ 2.54m (17" ~ 100") diagonal Screen size

Lamp info

Light source type LED life 20,000 hours

Optical

Throw ratio 1.5:1 Projection distance (m) 0.55m - 3.23m Zoom type Fixed Focal length (mm) 14.95 Native offset 100%

Connectivity

Connections Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card

1 x USB-A reader Outputs 1 x Audio 3.5mm

General

Noise level (typical) 30dB Noise level (max) 32dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 2D compatibility

3D compatibility SVGA 120Hz, XGA 120Hz

3D 3D ready

Security bar, Kensington Lock, Password protected interface Security OSD / display languages 13 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish

5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m Operating conditions

Card style Remote control Speaker count

Watts per speaker 1\/\ In the box Carry bag

Universal I/O cable AC power cord Remote control Battery Basic user manual

Input lag 16.00ms Optional wireless models WUSB

Power

100 ~ 240V, 50 ~ 60Hz Power supply

0.5W Power consumption (standby) 45W Power consumption (min) Power consumption (max) 65W

Weight and dimensions Dimensions (W x D x H) mm

105 x 106 x 39 Gross weight 1.31 kg 0.38 kg Net weight





